



BAKERLUX STATIONS

MODEL: BLS-3HTD-1H



NEMA 6-20P Plug

XAKHT-HCHS HALF Size Ventless System for LED/TOUCH Convection Ovens

Water Connection is required for proper installation, filtration is highly recommended to prevent scale build up. Drain line or floor drain is needed.


UL 710 Emissions



*For XAKHT-HCHS

Water Consumption Note* 10.3 oz from 3 hours and 30 minutes from the baking cycle. Therefore you would need to put the water consumption at less than 3 oz per hour.

TOUCH digital programmable controls:



9 BAKING STEPS



0 - inf TIMER

120° - 500° F TEMPERATURE

0-20-40-60-80-100% HUMIDITY

2 FAN SPEEDS

PROOFER CONTROL

99 PROGRAMS

WI-FI

DATA DRIVEN COOKING - CHAIN BASED APPLICATION

FEATURES


- Advanced airflow design & automatically reversible fan for even baking
- USB programming capability • 9 baking steps
- Digital programmable controls: Time, Temperature, Humidity
- Wi-Fi • Data driven cooking
- Heat settings from 175°-500° F
- Saves up to 99 programs with graphic control panel
- Handles 3 HALF size sheet pans (not included)
- 3 wire shelves included
- Cooking chamber: 13-1/4" H x 27-1/4" W x 19" D (4 cu. ft.)
- 10 hour timer or continuous on
- Light flashes and unit beeps at end of cycle
- Heavy duty stainless steel construction
- Heavy duty door & hinge construction
- Extra large motor for long lasting use
- 2-5/8" between shelves
- 1 fans; 3 fan speeds • Interior LED light
- Open Door/Auto shut off
- Includes electro valve for direct plumbed water connection
- "Cool-touch" double wall glass door opens from top
- Stackable with optional XWKQT-04EF-E Stacking Kit
- NSF; ETL to UL & CSA Standards/ listed by UNOX S.p.A.
- Energy Star rated • Chef Support - via phone
- 3 year Limited Warranty (two year On-site service & parts, 3rd year parts only)**
- **90 day warranty on light bulbs & gasket (not service center items); 30 days on glass; one year on motor
- 208-240 Volts / 2600-3300 Watts / 14 Amps / Single Phase / 60Hz
- NEMA 6-20P Plug



Incoming Water:

The bottom of the appliance contains 6.ft 7 in of pipe with a tee for connecting to the water supply (including mechanical filter and fitting (3/4") with non-return valve). A shut-off valve should be positioned between the water mains and the appliance.

We recommend that the end user have a standard ice-machine filter when using a humidity hookup.



OST-34A-C

Heavy-Duty aluminum Stand with casters for Half Size Ovens
Handles 10 halfsize sheet pans (not included)
Can hold 2 full size Cadco ovens with optional Stacking Kit

208-240 Volt

Drain line -or - floor drain is required.

Bakerlux Station Includes:



| Model | Color | Volts | Watts | Amps | Unit Dimensions |
|--------------|-----------|---------|-----------|------|------------------------------------|
| XAKHT-HCHS | Stainless | 208/240 | 200 | 1 | W: 23 22/32"H: 9 1/2" D: 28 10/32" |
| XAFT-03HS-TD | Stainless | 208/240 | 2600-3300 | 14 | W: 23.6875" H: 16" D: 25.5" |
| OST-034A-C | Stainless | N/A | N/A | N/A | W: 22.6875" H: 35" D: 26.75" |

Unit Dimensions

28.3125" L x 23.6875" W x 60.5" H

Shipping Unit Dimensions

Skid 1: 209lbs 48L x 40 Wx 68 H
CLASS 200

Made to Cadco Ltd. specifications by UNOX S.p.A., Italy NSF, ETL to UL & CSA Standards
We recommend that the end user have a standard ice-machine filter when using a humidity hookup.



www.cadco-ltd.com



860.738.2500



info@cadco-ltd.com