

BAKERLUX STATIONS

MODEL: BLS-4FLD-1













digital programmable controls:
















FEATURES

- Advanced airflow design & automatically reversible fan for even baking
- Digital programmable controls: Time, Temperature, Humidity
- 3 baking steps
- Heat settings from 175°-500° F
- Saves up to 99 programs with graphic control panel
- Handles 4 full size sheet pans (not included)
- Cooking chamber: 13-1/4" H x 27-1/4" W x 19" D (4 cu. ft.)
- 10 hour timer or continuous on
- Light flashes and unit beeps at end of cycle
- Heavy duty stainless steel construction
- Heavy duty door & hinge construction
- Extra large motor for long lasting use 2-5/8" between shelves
- 2 fan; 3 fan speedsInterior LED light
- Open Door/Auto shut off
- Includes electro valve for direct plumbed water connection
- "Cool-touch" double wall glass door opens from top
- NSF; ETL to UL & CSA Standards/ listed by UNOX S.p.A.
- Energy Star rated Chef Support via phone
- 3 year Limited Warranty (two year On-site service & parts, 3rd year parts only)**
- **90 day warranty on light bulbs & gasket (not service center items); 30 days on glass; one year on motor
- 208-240 Volts / 5900-7600 Watts / 32 Amps / Single Phase / 60Hz
- NEMA 6-50P Plug



Incoming Water:

The bottom of the appliance contains 6.ft 7 in of pipe with a tee for connecting to the water supply (including mechanical filter and fitting (3/4")




We recommend that the end user have a standardice-machine filter when using a humidity hookup.

OST-195-C

Heavy-Duty Aluminum Stand with casters for half size ovens Holds 10 half size sheet pans - not included

208-240

Bakerlux Station Includes:



Unit Dimensions 31"L x 31.5" W x 54" H

Shipping Unit Dimensions 224lbs 38"L x 35" W x 55" H Class 200

Made to Cadco Ltd. specifications by UNOX S.p.A., Italy NSF, MET to UL & CSA Standards We recommend that the end user have a standard ice-machine filter when using a humidity hookup.







860.738.2500

