



MODEL: BLS-4FLD-2H



XAKHT-HCFS Full Size Ventless System for LED/TOUCH Convection Ovens

Water Connection is required for proper installation, filtration is highly recommended to prevent scale build up. Drain line or floor drain is needed. **UL 710 Emissions**

Water Consumption Note* 10.3 oz from 3 hours and 30 minutes from the baking cycle. Therefore you would need to put the water consumption at less than 3 oz per hour.

LED digital programmable controls:


- 3** BAKING STEPS
- 0 - inf** TIMER
- 120° - 500° F** TEMPERATURE
- 0-20-40-60-80-100%** HUMIDITY
- 2** FAN SPEEDS
- PROOFER CONTROL**
- 99 PROGRAMS**
- 12 QUICK ACCESS**



Incoming Water:

The bottom of the appliance contains 6.6 ft 7 in of pipe with a tee for connecting to the water supply (including mechanical filter and fitting (3/4") with non-return valve). A shut-off valve should be positioned between the water mains and the appliance.

We recommend that the end user have a standard ice-machine filter when using a humidity hookup.



OST-195-CS
Heavy-Duty Aluminum Stand with Casters for Half Size Ovens
Handles 10 full size sheet pans (not included)
Can hold 2 full size Cadco ovens with optional stacking kit

208-240 Volt

FEATURES

- Advanced airflow design & automatically reversible fan for even baking
- 3 baking steps
- Digital programmable controls: Time, Temperature, Humidity
- Data driven cooking
- Heat settings from 175°-500° F
- Saves up to 99 programs with graphic control panel
- Handles 4 full size sheet pans (not included)
- 4 wire shelves included
- Cooking chamber: 13-1/4" H x 27-1/4" W x 19" D (4 cu. ft.)
- 10 hour timer or continuous on
- Light flashes and unit beeps at end of cycle
- Heavy duty stainless steel construction
- Heavy duty door & hinge construction
- Extra large motor for long lasting use
- 2-5/8" between shelves
- 2 fan speeds • Interior LED light
- Open Door/Auto shut off
- Includes electro valve for direct plumbed water connection
- "Cool-touch" double wall glass door opens from top
- Stackable with optional XWKQT-04EF-E Stacking Kit
- NSF; ETL to UL & CSA Standards/ listed by UNOX S.p.A.
- Energy Star rated • Chef Support - via phone
- 3 year Limited Warranty (two year On-site service & parts, 3rd year parts only)**
- **90 day warranty on light bulbs & gasket (not service center items); 30 days on glass; one year on motor
- 208-240 Volts / 5900-7600 Watts / 32 Amps / Single Phase / 60Hz
- NEMA 6-50P Plug

Drain line -or - floor drain is required.

Bakerlux Station Includes:



Model	Color	Volts	Watts	Amps	Unit Dimensions		
XAKHT-HCFS	Stainless	208-240	200	1	W: 31.5"	H: 9.5"	D: 33.5625"
XAFT-04FS-LD	Stainless	208-240	5900-7600	32	W: 31.5"	H: 19"	D: 31"
OST-195-CS	Stainless	N/A	N/A	N/A	W: 30.5"	H: 21.875"	D: 26.75"

Unit Dimensions

33.5625" L x 31.5" W x 71.875" H

Shipping Unit Dimensions

Skid 1: 213 lbs 38" L x 35" W x 48" H
Skid 2: 228 lbs 38" L x 35" W x 27" H
CLASS 200

Made to Cadco Ltd. specifications by UNOX S.p.A., Italy NSF, MET to UL & CSA Standards
We recommend that the end user have a standard ice-machine filter when using a humidity hookup.

