



# HALF SIZE HEAVY DUTY MANUAL



## Model: XAF-113

Half Size, 3 Shelf, Manual Control, 120v (With Humidity)  
Unit Dimensions (W" x H" x D"): 23 5/8 x 16 7/8 x 28 1/8  
Cavity Size (W" x H" x D"): 19 1/2 x 10 x 15 1/2; 1.75 cft.  
One fan. NEMA 5-15P plug  
Volts: 120 Watts: 1440 Amps: 12  
Shipping Weight (lbs.): 120\*



NEMA  
5-15P  
Plug

Stands available: OST-34A-C, OST-34A-CS.

Heavy-Duty 2-Oven Stand also available: OV-HDS

Stackable with CXC651 Stacking Kit

Model	Color	Volts	Watts	Amps	Unit Dimensions	Unit Wt.	Ship Wt.	Ship Dimensions	Cube
XAF-113	Stainless	120	1440	12	w:23 5/8", h:16 7/8", d:28 1/8"	74 lbs.	120* lbs.	w:42", h:21 7/8", d:48"*	24.36*



## Model: XAF-133

Half Size, 4 Shelf, Manual Control, 220v (With Humidity)  
Unit Dimensions (W" x H" x D"): 23 5/8 x 20 x 28 1/8  
Cavity Size (W" x H" x D"): 19 1/2 x 13 x 15 1/2; 2.27 cft.  
One fan. NEMA 6-20P plug  
Volts: 208-240 Watts: 2500-3250 Amps: 20  
Shipping Weight (lbs.): 125\*



NEMA  
6-20P  
Plug

Stands available: OST-34A-C, OST-34A-CS.

Heavy-Duty 2-Oven Stand also available: OV-HDS

Stackable with CXC651 Stacking Kit

Model	Color	Volts	Watts	Amps	Unit Dimensions	Unit Wt.	Ship Wt.	Ship Dimensions	Cube
XAF-133	Stainless	208-240	2500-3250	20	w:23 5/8", h:20", d:28 1/8"	80 lbs.	125* lbs.	w:42", h:25", d:48"*	29.17*

**We recommend that the end user have a standard ice-machine filter when using a humidity hookup.**

- 3" between shelves
- "Cool-touch" double wall glass door
- Oven cavity is wrapped in high "R" value insulation
- 60 minute timer or continuous on
- Timer beeps at end of cycle
- Heat settings from 175°-500° F
- Heavy duty stainless steel construction
- High temperature motor bearings
- Heavy duty door & hinge construction
- LED light in door
- Dimensions are designed to accommodate modular stacking for customized configuration
- 2 year Limited Warranty (one year On-site service & parts, 2nd year parts only)\*\*
- 90 day warranty on light bulbs & gasket (not service center items); 30 days on glass; one year on motor
- Freight class 200 NOTE: This model must ship by truck, not UPS



www.cadco-ltd.com



860.738.2500



info@cadco-ltd.com