



FULL SIZE HEAVY DUTY MANUAL



Model: XAF-183

Full Size, 3 Shelf, Manual Control, 220v (With Humidity)

Unit Dimensions (W" x H" x D"): 31 1/2 x 19 7/8 x 32

Cavity Size (W" x H" x D"): 27 1/4 x 10 x 18 3/4; 3 cft.

One fan. NEMA L6-30 plug

Volts: 208-240 Watts: 4600 Amps: 20



NEMA
L6-30
Plug

Shipping Weight (lbs.): 180*

Stands available: OST-195-C, OST-195-CS.

Stackable with CXC646 Stacking Kit

Model	Color	Volts	Watts	Amps	Unit Dimensions	Unit Wt.	Ship Wt.	Ship Dimensions	Cube
XAF-183	Stainless	208-240	4600	20	w:31 1/2", h:19 7/8", d:32"	112 lbs.	180* lbs.	w:42", h:20 7/8", d:48"*	24.36*

*includes dimensions & weight (approx. 40 lbs.) of shipping skid



Model: XAF-193

Full Size, 4 Shelf, Manual Control, 220v (With Humidity)

Unit Dimensions (W" x H" x D"): 31 1/2 x 23 x 32

Cavity Size (W" x H" x D"): 27 1/4 x 13 x 18 3/4; 3.85 cft.

Two fans. NEMA L6-30 plug

Volts: 208-240 Watts: 5600 Amps: 23.3



NEMA
L6-30
Plug

Shipping Weight (lbs.): 190*

Model	Color	Volts	Watts	Amps	Unit Dimensions	Unit Wt.	Ship Wt.	Ship Dimensions	Cube
XAF-193	Stainless	208-240	5900	24.6	w:31 1/2", h:23", d:32"	134 lbs.	190* lbs.	w:42", h:24", d:48"*	28*

*includes dimensions & weight (approx. 40 lbs.) of shipping skid

We recommend that the end user have a standard ice-machine filter when using a humidity hookup.

3" between shelves

"Cool-touch" double wall glass door

Oven cavity is wrapped in high "R" value insulation

60 minute timer or continuous on

Timer beeps at end of cycle

Heat settings from 175°-500° F

Heavy duty stainless steel construction

High temperature motor bearings

Heavy duty door & hinge construction

LED light in door

Dimensions are designed to accommodate modular stacking for customized configuration

2 year Limited Warranty (one year On-site service & parts, 2nd year parts only)**

90 day warranty on light bulbs & gasket (not service center items); 30 days on glass; one year on motor

Freight class 200 NOTE: This model must ship by truck, not UPS



www.cadco-ltd.com



860.738.2500



info@cadco-ltd.com