

Countertop Convection Oven

MODEL: XAFT-04FS-TR

Heavy-Duty 4 Shelf Countertop Convection Oven with Digital Controls & Humidity





The bottom of the appliance contains 6.ft 7 in of pipe with a tee for connecting to the water supply (including mechanical filter and fitting (3/4")

with non-return valve). A shut -off valve should be positioned between the water mains and the appliance.

We recommend that the end user have a standardice-machine filter when using a humidity hookup.

FEATURES

- Advanced airflow design & automatically reversible fan for even baking
- USB programming capability 9 baking steps
- Digital programmable controls: Time, Temperature, Humidity
- Wi-Fi
 Data driven cooking
- Heat settings from 175°-500° F
- Saves up to 99 programs with graphic control panel
- Handles 4 full size sheet pans (not included)
- 4 wire shelves included
- Cooking chamber: 13-1/4" H x 27-1/4" W x 19" D (4 cu. ft.)
- 10 hour timer or continuous on
- Light flashes and unit beeps at end of cycle
- Heavy duty stainless steel construction
- Heavy duty door & hinge construction
- Extra large motor for long lasting use
- 2-5/8" between shelves

- 2 fans; 3 fan speeds
- Interior LED light
- Auto shut off when door is opened
- Includes electro valve for direct plumbed water connection
- "Cool-touch" double wall glass door opens on right
- Stackable with optional XWKQT-04EF-E Stacking Kit
- NSF; ETL to UL & CSA Standards/ listed by UNOX S.p.A.
- Energy Star rated
- Chef Support via phone
- 3 year Limited Warranty (two year On-site service & parts, 3rd year parts only)**
- **90 day warranty on light bulbs & gasket (not service center items); 30 days on glass; one year on motor
- 208-240 Volts / 5900-7600 Watts / 32 Amps / Single Phase / 60HZ
- NEMA 6-50P Plug
- Freight class 200 NOTE: This model must ship by truck, not UPS

OPTIONAL ACCESSORIES:

- XAKPT-08FS-C Proofer
- XWKQT-04EF-E Stacking Kit
- XAKHT-HCFS Ventless HoodSt
- Stands: OST-195-C, OST-195-CS

Mod	el	Color	Volts	Watts	Amps	Unit Dimensions	Unit Wt.	Ship Wt	Carton Dimensions	Cube
XAFT-04F	S-TR	Stainless	208-240	5900-7600	32	w:311/2", h:19", d:31"	140 lbs.	190* lbs.	w:42", h:261/4", d:48" *	30.63*

Made to Cadco Ltd.specifications by UNOX S.p.A., Italy

NSF, ETL to UL & CSA Standards

Cadco Model XAFT-04FS-TR = UNOX Model XAFT-04FS-ETRV-US *includes dimensions & weight (approx. 40 lbs.) of shipping skid





