

MODEL: XAFT-04HS-LD

Heavy-Duty 4 Shelf Countertop Convection Oven with Digital Controls & Humidity













Incoming Water:

The bottom of the appliance contains 6.ft 7 in of pipe with a tee for connecting to the water supply (including mechanical liter and fitting (3/4")



with non-return valve). A shut -off valve should be positioned between t he water mains and the appliance.

We recommend that the end user have a standardice-machine filter when using a humidity hookup.

FEATURES

- Advanced airflow design & automatically reversible fan for even baking
- 3 baking steps
- Digital programmable controls: Time, Temperature, Humidity
- Heat settings from 175°-500° F
- Saves up to 99 programs including 12 "Quick Access" programs
- Handles 4 half size sheet pans (not included)
- 4 wire shelves included
- Cooking chamber: 13-1/4" H x 19-1/4" W x 14" D
 (2.1 cu. ft.)
- 10 hour timer or continuous on
- Light flashes and unit beeps at end of cycle
- Heavy duty stainless steel construction
- Heavy duty door & hinge construction
- Extra large motor for long lasting use
- 2-5/8" between shelves

- 1 fan; 2 fan speeds
- Interior LED light
- Auto shut off when door is opened
- Includes electro valve for direct plumbed water connection
- "Cool-touch" double wall glass door
- Stackable with optional XWKQT-00HS-E Stacking Kit
- NSF; ETL to UL & CSA Standards/ listed by UNOX S.p.A.
- Energy Star rated
- Chef Support via phone
- 3 year Limited Warranty (two year on-site service & parts, 3rd year parts only)**
- **90 day warranty on light bulbs & gasket (not service center items); 30 days on glass; one year on motor
- 208-240 Volts / 2900-3800 Watts / 16 Amps / Single Phase / 60Hz
- NEMA 6-20P Plug
- Freight class 200 NOTE: This model must ship by truck, not UPS

OPTIONAL ACCESSORIES:

- XAKPT-08HS-C Proofer
- XAKHT-HCHS Ventless HoodXWKQT-00HS-E Stacking Kit
- Stands: OST-34A-C, OST-34A-CS
- Heavy-Duty 2-Oven Stand: OV-HDS

Model	Color	Volts	Watts	Amps	Unit Dimensions	Unit Wt.	Ship Wt.	Carton Dimensions	Cube
XAFT-04HS-LD	Stainless	208-240	2900-3800	16	w:23.6875", h:19", d:25.5"	93 lbs.	139* lbs.	w:42", h:261/4", d:48"*	30.63*

Made to Cadco Ltd. specifications by UNOX S.p.A., Italy

•NSF, ETL to UL & CSA Standards

Cadco Model XAFT-04HS-LD = UNOX Model XAFT-04HS-ELDV-US *includes dimensions & weight (approx. 40 lbs.) of shipping skid





